

MONITORING REPORT

CARBON OFFSET UNIT (CoU) PROJECT



Title	:	2.1 MW Wind Power Project by SVPL
Version	:	2.0
MR Date	:	15/02/2025
First CoU Issuance Period	:	2 years and 6 months
First Monitoring Duration	:	01/07/2021 to 31/12/2023



Monitoring Report (MR)

CARBON OFFSET UNIT (CoU) PROJECT

BASIC INFORMATION				
Title of the project activity	2.1 MW Wind Power Project by SVPL			
UCR Project Registration Number	445			
Version	2.0			
Completion date of the MR	15/02/	2025		
Monitoring period number and	Monit	oring Period Number: 01		
duration of this monitoring period	Durati month	on of this monitoring Period: 2 years and 6 s		
	(First 31/12/	and last days included (01/07/2021 to 2023)		
Project participants	Creduce Technologies Private Limited (Aggregator)			
	M/s Simpolo Vitrified Private Limited (Proje			
	Proponent)			
Host Party	India			
Applied methodologies and	Applied Baseline Methodology:			
standardized baselines		I. D: "Grid connected renewable electricity		
	genera	tion", version 18		
Sectoral Scope	01 Ene	ergy industries		
	(Renewable/Non-Renewable Sources)			
Estimated amount of GHG emission				
reductions for this monitoring period				
	2022	4359		
	2023	4280		
Total:	10518 CoUs (10518 tCO ₂ e)			

SECTION - A - Description of project activity

A.1 Purpose and General description of Carbon offset Unit (CoU) project activity

The proposed project titled under UCR is "2.1 MW Wind Power Project by SVPL", which is wind power project located in Kutch district in the state of Gujarat (India). The purpose of this plant installation and power generation is for captive consumption. The project is an operational activity with continuous reduction of GHG, currently being applied under "Universal Carbon Registry" (UCR).

A.1.1 Purpose of the project activity:

The project activity is a renewable power generation activity which incorporates installation and operation of single Wind Turbine Generator (WTG) having capacity of 2.1 MW manufactured and supplied by Suzlon Energy respectively in district Kutch of the state of Gujarat in India. This project has been promoted by M/s Simpolo Vitrified Pvt Ltd.

The details of wind turbine is given below -

Project owner Name	Village	District	COD	State	Project Co- ordinates
Simpolo Vitrified Pvt. Ltd.	Sukhsan	Kutch	30/06/2021	Gujarat	23°17'04.5" N 69°18'17.8" E

The project activity aims to harness the kinetic energy of wind (a renewable source) to generate electricity. Wheeling agreement is signed between Panschim Gujarat Vij Company Limited (PGVCL) and PP. The project activity has been helping in greenhouse gas (GHG) emission reduction by using renewable resources (wind energy) for generating power which otherwise would have been generated using grid mix power plants, which is dominated by fossil fuel based thermal powerplants. Currently, the NEWNE grid is connected to large numbers of fossil fuel-based power plants. Hence, project activity is displacing the gross electricity generation i.e., 11687.709 MWh from the NEWNE grid, which otherwise would have been imported from the NEWNE grid.

Since the project activity generates electricity through wind energy, a clean renewable energy source it will not cause any negative impact on the environment and thereby contributes to climate change mitigation efforts

The project activity doesn't involve any GHG emission sources. The annual and total CO₂e emission reduction by the project activity over the defined monitoring period is as per **Annexure I.**

A.1.2 Description of the installed technology and equipment:

The project activity involves one WTG having a capacity of 2.1 MW manufactured and supplied by Suzlon Energy. The other salient features of the technology are:

The wind turbine is used to produce electricity using the kinetic energy of the wind. This is transformed

into electrical energy using wind turbines or wind energy conversion systems. Wind first hits a turbine's blades, causing them to rotate and turn the turbine connected to them. That changes the kinetic energy to rotational energy, by moving a shaft which is connected to a generator, and thereby producing electrical energy through electromagnetism.

Below is a description of the different components of a Wind Turbine Generator.

- 1. **Main Tower:** The main support tower is made of steel, finished in a number of layers of protective paint to shield it against the elements. The tower is tall enough to ensure the rotor blade does not interfere with normal day-to-day operations at ground level.
- 2. **Rotor Blades:** The rotor blades are the three (usually three) long thin blades that attach to the hub of the nacelle. These blades are designed to capture the kinetic energy in the wind as it passes, and convert it into rotational energy.
- 3. **Nacelle:** The nacelle is the 'head' of the wind turbine, and it is mounted on top of the support tower. The rotor blade assembly is attached to the front of the nacelle. It contains all the major parts of the WEG.
- 4. **Hub:** The hub of the wind turbine is the component that connects the blades to the main shaft and ultimately to the rest of the tower. The hub transmits and withstands all the loads generated by the blades.
- 5. **Main Shaft:** It is a piece of metal in the form of a tube that constitutes the most important spinning constituent since it conveys the energy from the wind turbine blades to the other parts of the wind turbine.
- 6. **Gear Box:** A gearbox is often used in a wind turbine to increase the rotational speed from a lowspeed main shaft to a high-speed shaft connecting with an electrical generator. Gears in wind turbine gearboxes are subjected to severe cyclic loading due to variable wind loads that are stochastic in nature.
- 7. **Brake:** A wind turbine rotor brake is a brake placed next to the gearbox that reduces the rotational speed of the blade assembly, fixes the blade so that it does not rotate in the case of power transmission maintenance or power generator rest, and in an emergency.
- 8. **Turbine generator:** The turbine generator is the component that turns the rotational energy in the high-speed output shaft from the gearbox into an electrical current. The electrical principle of electromagnetic induction shows that while a magnet is moving past a coil of wire, an electric current is created (or "induced") in the wire.

A.1.3 Relevant dates for the project activity (e.g., construction, commissioning, continued operation periods, etc.)

The duration of the crediting period corresponding to the monitoring period is covered in this monitoring report.

UCR Project ID	:	455
Start Date of Crediting Period	:	01/07/2021

A.1.4 Total GHG emission reductions achieved or net anthropogenic GHG removals by sinks achieved in this monitoring period.

Summary of the project activity and ERs generated for the monitoring period					
Start date of this Monitoring Period	01/07/2021				
Carbon credits claimed up to	31/12/2023				
Total ERs generated (tCO ₂ e)	10518 tCO ₂ e				
Leakage Emission	0				
Project Emission	0				

The total GHG emission reductions achieved in this monitoring period are as follows:

A.1.5 Baseline Scenario

As per the approved consolidated methodology AMS-I.D. Version 18, if the project activity is the installation of a new grid-connected renewable power plant/unit, the baseline scenario is the following: "The baseline scenario is that the electricity delivered to the grid by the project activity would have otherwise, been generated by the operation of grid-connected power plants and by the addition of new generation sources into the grid".



Figure 1 Baseline Scenario

A.2 Location of Project Activity

The project location is situated in the state of Gujarat. The project site is well connected by district and village roads to the nearest town. The geographic coordinates of the project locations have been provided below.

Project owner Name	Village	Taluka	District	State	Project Co-ordinates
Simpolo Vitrified Pvt. Ltd.	Sukhsan	Nakhtrana	Kutch	Gujarat	22°26'13.8"N 70°17'06.2"E

The representative location map is included below:



Figure-1- Location of the project activity (courtesy: Google Images and <u>www.mapofindia.com</u>)

A.3 Parties and project participants

Party (Host)	Participants		
India	Creduce Technol	ogie	es Private Limited (Aggregator)
	Contact person	:	Shailendra Singh Rao
	Mobile	:	+91 9016850742, 9601378723
	Address: 2-O-13, 327001, India	14 I	Housing BoardColony, Banswara, Rajasthan -

M/s Simpolo Vitrified Pvt. Ltd.
Address: Survey no. 600, 600/1, P1, 600/1 P2, 600/1 P3, 600/4 P4,
Ghuntu Morbi – 363642, Gujarat - India

A.4 Methodologies and standardized baselines

Sectoral Scope	:	01 Energy industries (Renewable/Non-Renewable Sources)
Туре	:	Renewable energy projects
Category	:	AMS-I. D: "Grid connected renewable electricity generation", Version 18

A.5 Crediting period of project activity

Start date of the crediting period: 01/07/2021

Crediting period corresponding to this monitoring period: 2 years and 6 months

01/07/2021 to 31/12/2023 (Both dates are inclusive)

A.6 Contact information of responsible persons/entities

Contact person	:	Shailendra Singh Rao
Mobile	:	+91 9016850742, 9601378723
Address	:	2-O-13,14 Housing Board Colony,
		Banswara, Rajasthan -327001, India

SECTION - B - Implementation of project activity

B.1 Description of implemented registered project activity

B.1.1 Provide information on the implementation status of the project activity during this monitoring period in accordance with UCR PCN

The project consists of one WTG with a capacity of 2.1MW which was commissioned by the Gujarat Energy Development Agency (GEDA), Government of Gujarat at District Kutch. M/s SVPL. is the owner of this project. The project generates clean energy by utilizing the kinetic energy of the wind.

B.1.2 For the description of the installed technology, technical process, and equipment, include diagrams, where appropriate

The project activity involves one WTG which is manufactured and supplied by Suzlon Energy with an installed capacity of 2.1 MW. The connectivity of the WTG is to a central Monitoring Station (CMS) through a high-speed WLAN modem or fiber optic cable which helps in providing real-time status of the turbine at CMS with easy GUI (Graphical User Interface) and the ability to monitor the functioning of the turbine from CMS. The life of the WTG is 20 years as per manufacturer specifications.

Sr. No	Item	Description
1	WF Capacity	2.1 MW
2	Make of WTG	Suzlon Energy
3	No. of WTG	1 nos
4	Rotor diameter	111.8m
5	Rotor swept area	9,852m ²
6	Rated power	2.1 MW
7	Cut in wind speed	3.0m/s
8	Rated wind speed	12.5m/s
9	Cut out wind speed	30.0m/s (3-second average)
		21.0m/s (10-minute average)
10	Tower Hub heights	90m 120m 140m

Technical details for the turbine with a capacity of 2.1 MW manufactured by Suzlon Energy are as follows:

11	Tower type	Steel Tubular Hybrid Lattice
12	Blade Make	Suzlon SB54
13	Generator frequency	50Hz / 60Hz

B.2 Do no harm or impact test of the project activity.

There was no harm identified from the project and hence no mitigation measures are applicable.

Rational: as per 'Central Pollution Control Board (Ministry of Environment & Forests, Govt. of India)', the final document on the revised classification of Industrial Sectors under Red, Orange, Green, and White Categories (07/03/2016), has been declared that wind project activity falls under the "White category". White Category projects/industries do not require any Environmental Clearance such as 'Consent to Operate' from PCB as the such project does not lead to any negative environmental impacts. Additionally, as per Indian Regulations, Environmental, and Social Impact Assessment is not required for wind projects.

The Government of India has stipulated the following indicators for sustainable development in the interim approval guidelines for such projects which are contributing to GHG mitigations. The Ministry of Environment, Forests & Climate Change, has stipulated economic, social, environmental, and technological well-being as the four indicators of sustainable development. It has been envisaged that the project shall contribute to sustainable development using the following ways:

Social well-being: The project would help in generating direct and indirect employment benefits accruing out of ancillary units for manufacturing towers for the erection of the wind turbine generator and for maintenance during the operation of the project activity. It will lead to the development of infrastructure around the project area in terms of improved road network etc. and will also directly contribute to the development of renewable infrastructure in the region.

Environmental well-being: The project utilizes wind energy for generating electricity which is a clean source of energy. The project activity will not generate any air pollution, wind pollution, or solid waste to the environment which otherwise would have been generated through fossil fuels. Also, it will contribute to the reduction of GHG emissions. Thus, the project causes no negative impact on the surrounding environment contributing to environmental well-being.

Economic well-being: Being a renewable resource, using wind energy to generate electricity contributes to the conservation of precious natural resources. The project contributes to economic sustainability through the promotion of decentralization of economic power, leading to the diversification of the national energy supply, which is dominated by conventional fuel-based generating units. Locally, improvement in infrastructure will provide new opportunities for industries and economic activities to be set up in the area. Apart from getting better employment opportunities, the local people will get better prices for their land, thereby resulting in overall economic development.

Technological well-being: The project activity leads to the promotion of a 2.1 MW WTG in the region and will promote practice for small-scale industries to reduce the dependence on carbon-intensive grid supply to meet the captive requirement of electrical energy and also increase energy availability and improve quality of power under the service area. Hence, the project leads to technological well-being.

SDG Goals	Targeted SDG	Targeted Indicator (SDG Indicator)
7 AFFORDABLE AND CLEAN ENERGY	7.2: By 2030, increase substantially the share of renewable energy in the global energy mix	 7.2.1: Renewable energy share in the total final energy consumption The project activity will generate clean energy, which with increased shared will increase the affordability at a cheaper rate to end user. The project activity will utilize wind energy (renewal resource) to generate power. The project activity will increase the share of renewable resource-based electricity to global mix of energy consumption
8 DECENT WORK AND ECONOMIC GROWTH	 8.5: By 2030, achieve full and productive employment and decent work for all women and men, including for young people and persons with disabilities, and equal pay for work of equal value Target: Training, O&M staff 	 8.5.1: Average hourly earnings of female and male employees, by occupation, age, and persons with disabilities. This project activity generates additional employment for skilled and unskilled, also the project situated in remote area will provide employment opportunities to unskilled people from villages. The training on various aspect including safety, operational issues and developing skill set will also be provided to employees

The project activity contributes to the following SDGs.

		This project will achieve full and productive employment and decent work for all women and men, including for young people and persons with disabilities, and equal pay for work of equal value
13 CLIMATE	 13.2: Integrate climate change measures international policies strategies and planning. ➤ Target: 10518 tCO₂/y 	 13.2.1: Number of countries that have the establishment or operationalization of an integrated policy/ strategy/ plan which increases their ability to adapt to the adverse impacts of climate change, and foster climate resilience and low greenhouse gas emissions development in a manner that does not threaten food production (including a national adaptation plan, nationally determined contribution, national communication, biennial update report or other) This 2.1 MW wind project meets the SDG 13 goal by saving fossil fuel and producing clean energy. SDG 13 on clean energy is closely related and complementary. In a Greenfield project, electricity delivered to the grid by the project would have otherwise been generated by the operation of grid-connected power plants. Thereby the project activity reduces the dependence on fossil fuel-based generation units and as there are no associated emissions with this project it contributes to the

	reduction of greenhouse gas (GHG)
	emissions.

B.3 Baseline Emissions

The baseline scenario identified at the MR stage of the project activity is:

In the absence of the project activity, the equivalent amount of electricity would have been imported from the grid (which is connected to the unified Indian Grid system (NEWNE Grid)), which is carbon intensive due to being predominantly sourced from fossil fuel-based power plants. Hence, the baseline scenario of the project activity is the grid-based electricity system, which is also the pre-project scenario.

Schematic diagram showing the baseline scenario:

Baseline Scenario:



Project Scenario:



Thus, this project activity was a voluntary investment that replaced an equivalent amount of electricity from the Indian grid. The project proponent was not bound to incur this investment as it was not mandatory by national and sectoral policies. Thus, the continued operation of the project activity would continue to replace fossil fuel-based power plants and fight against the impacts of climate change. The PP hopes that revenues from the carbon credits generated will help repay the loans and help in the continued maintenance of this project activity.

B.4. De-bundling

This project activity is not a bundled component of a larger project activity.

SECTION - C - Application of methodologies and standardized baselines

Sectoral scope	:	01, Energy industries (Renewable/Non-renewable sources)
Туре	:	I-Renewable energy projects
Category	:	AMS. I.D. (Title: "Grid connected renewable electricity generation", version 18)

C.1 References to methodologies and standardized baselines

C.2 Applicability of methodologies and standardized baselines

The project activity involves the generation of grid-connected electricity from the construction and operation of a new wind power-based project for captive consumption. A wheeling agreement is signed between M/s Simpolo Vitrified Private Limited and PGVCL i.e., state utility.

The project activity has an installed capacity of 2.1 MW which will qualify for a small-scale project activity under Type-I of the small-scale methodology. The project status is corresponding to the methodology AMS-I.D., version 18, and the applicability of the methodology is discussed below:

Applicability Criterion	Project Case
 This methodology comprises renewable energy generation units, such as photovoltaic, hydro, tidal/wave, wind, geothermal and renewable biomass: (a) Supplying electricity to a national or a regional grid; or (b) Supplying electricity to an identified consumer facility via national/regional grid through a contractual arrangement such as wheeling. 	The project activity is a renewable energy project i.e., a wind power project which falls under applicability criteria option 1 (b). i.e., Supplying electricity to an identified consumer facility via national/regional grid through a contractual arrangement such as wheeling.
 2. This methodology is applicable to project activities that: (a) Install a greenfield plant; (b) Involve a capacity addition in (an) existing plant(s); (c) Involve a retrofit of (an) existing plant(s); (d) Involve a rehabilitation of (an) existing plant(s)/unit(s); or (e) Involve a replacement of (an) existing plant(s). 	The option (a) of applicability criteria 2 is applicable as project is a greenfield plant/unit. Hence the project activity meets the given applicability criterion.

3. Hydro power plants with reservoirs that satisfy at least one of the following conditions are eligible to apply this methodology:a) The project activity is implemented in the existing reservoir, with no change in the volume of the reservoir; or	The project activity involves the installation of 2.1 MW WTG; hence, this criterion is not applicable.
b) The project activity is implemented in the existing reservoir, where the volume of the reservoir(s) is increased and the power density as per definitions given in the project emissions section, is greater than 4 W/m ² .	
c) The project activity results in new reservoirs and the power density of the power plant, as per definitions given in the project emissions section, is greater than 4 W/m ² .	
4. If the new unit has both renewable and non-renewable components (e.g., a wind/diesel unit), the eligibility limit of 15 MW for a small-scale CDM project activity applies only to the renewable component. If the new unit co-fires fossil fuel, the capacity of the entire unit shall not exceed the limit of 15 MW.	The proposed project is a 2.1 MW wind power project, i.e., the only component is a renewable power project below 15MW, thus the criterion is not applicable to this project activity.
5. Combined heat and power (co-generation) systems are not eligible under this category.	The project is a wind power project and thus, the criterion is not applicable to this project activity.
6. In the case of project activities that involve the capacity addition of renewable energy generation units at an existing renewable power generation facility, the added capacity of the units added by the project should be lower than 15 MW and should be physically distinct from the existing units.	The proposed project is a greenfield 2.1 MW wind power project, i.e., the only component is a renewable power project below 15 MW, thus the criterion is not applicable to this project activity.
7. In the case of retrofit, rehabilitation or replacement, to qualify as a small-scale project, the total output of the retrofitted, rehabilitated or replacement power plant/unit shall not exceed the limit of 15 MW.	The proposed project is a greenfield 2.1 MW wind power project, i.e., the only component is a renewable power project below 15 MW, thus the criterion is not applicable to this project activity.
8. In the case of landfill gas, waste gas, wastewater treatment and agro-industries projects, recovered methane emissions are eligible under a relevant Type III category. If the recovered methane is used for electricity generation for supply to a grid, then the baseline for the electricity component shall be in accordance with procedure prescribed under this methodology. If the recovered methane is used for	The proposed project is a greenfield 2.1MW wind power project; hence, this criterion is not applicable to this project activity.

heat generation or cogeneration other applicable Type-I methodologies such as "AMS-I.C.: Thermal energy production with or without electricity" shall be explored.	
9. In case biomass is sourced from dedicated plantations, the applicability criteria in the tool "Project emissions from cultivation of biomass" shall apply.	No biomass is involved, the project is only a wind power project and thus the criterion is not applicable to this project activity.

C.3 Applicability of double counting emission reductions

The project was not applied under any other GHG mechanism. Hence the project will not cause double accounting of carbon credits (i.e., CoUs).

C.4 Project boundary, sources, and greenhouse gases (GHGs)

As per applicable methodology AMS-I.D. Version 18, "The spatial extent of the project boundary includes the project power plant and all power plants connected physically to the electricity system." Thus, the project boundary includes the Wind Turbine Generator and the Indian grid system.

Source		Gas	Included?	Justification/Explanation
		CO_2	Yes	Main emission source
ine	Grid-	CH ₄	No	Minor emission source
Basel	electricity	N ₂ O	No	Minor emission source
generation	generation	Other	No	No other GHG emissions were emitted from the project
	Creanfield		No	No CO ₂ emissions are emitted from the project
ject	Greenfield Electric Power project	CH ₄	No	Project activity does not emit CH ₄
Pro		N ₂ O	No	Project activity does not emit N ₂ O
	Activity	Other	No	No other emissions are emitted from the project

C.5 Establishment and description of the baseline scenario

As per the approved consolidated methodology AMS-I.D. Version 18, if the project activity is the

installation of a new grid-connected renewable power plant/unit, the baseline scenario is the following:

"The baseline scenario is that the electricity delivered to the grid by the project activity would have otherwise been generated by the operation of grid-connected power plants and by the addition of new generation sources into the grid".

The project activity involves setting up of a new WTG to harness the wind energy and use it for captive consumption i.e., the Indian grid system through wheeling and banking arrangement. In the absence of the project activity, the equivalent amount of power would have been generated by the operation of gridconnected fossil fuel-based power plants and by the addition of new fossil fuel-based generation sources into the grid. The power produced from other conventional sources which are predominantly fossil fuel based. Hence, the baseline for the project activity is the equivalent amount of power produced at the Indian grid.

A "grid emission factor" refers to a CO₂ emission factor (tCO₂/MWh) that will be associated with each unit of electricity provided by an electricity system. The UCR recommends an emission factor of 0.9 tCO₂/MWh for the 2013 - 2020 years as a conservative estimate for Indian projects not previously verified under any GHG program. Also, for the vintage 2021-2023, the combined margin emission factor calculated from the CEA database in India results in higher emissions than the default value. Hence, the same emission factor has been considered to calculate the emission reduction under a conservative approach.

C.5.1 Net GHG Emission Reductions and Removals

Thus, ER_v $= BE_v - PE_v - LE_v$

Where:

 ER_v = Emission reductions in year y (tCO_2/y)

BEv = Baseline Emissions in year y (t CO_2/y)

 PE_v = Project emissions in year y (tCO_2/y)

LE_v = Leakage emissions in year y (tCO_2/y)

Baseline Emissions

Baseline emissions include only CO₂ emissions from electricity generation in power plants that are displaced due to the project activity. The methodology assumes that all project electricity generation above baseline levels would have been generated by existing grid-connected power plants and the addition of new grid-connected power plants. The baseline emissions are to be calculated as follows:

BE_y		$= EG_{PJ,y} \times EF_{grid,y}$
BE_y	=	Baseline emissions in year y (tCO ₂)
$EG_{PJ,y}$	=	Quantity of net electricity generation that is produced and fed into the grid as a
		result of the implementation of the CDM project activity in year y (MWh)
$EF_{grid,y}$	=	UCR recommended emission factor of 0.9 tCO ₂ /MWh has been considered.
		(Reference: General Project Eligibility Criteria and Guidance, UCR Standard,
		page 4)

Hence

	Baseline Emissions Calculation				
Sr. No.	Year	EGpy (MWh)	$\mathbf{EF}_{\mathbf{grid},\mathbf{y}}$	BEy	
1	2021	2088.502	0.9	1879	
2	2022	4843.426	0.9	4359	
3	2023	4755.781	0.9	4280	
	BE (tCO ₂ e) for the period of 2021-2023			10518	

Estimated annual baseline emission reductions (BE_y)

= 11687.709 MWh *0.9 tCO₂/MWh

 $= 10518 \text{ tCO}_2$

• Project Emissions

As per paragraph 39 of AMS-I.D. version-18, "For most renewable energy project activities, $PE_y = 0$.

This is a wind power project, there is no project emission occurring from biomass and fossil fuel consumption.

Thus, PE = 0

• Leakage Emission

As per paragraph 42 of AMS-I.D. version-18, General guidance on leakage in biomass project activities shall be followed to quantify leakages pertaining to the use of biomass residues.

Hence, all projects other than Biomass projects have zero leakage.

LE =

The actual emission reduction achieved during the first CoU period is calculated below:

Hence Net GHG emission reduction, = $10518-0-0 = 10518 \text{ tCO}_2$ (i.e., 10518 CoUs)

C.6 Prior History

The project activity is not registered under any program.

C.7 Changes to the start date of crediting

0

The crediting period under UCR has been considered from the date of the generation of electricity. There is no change in the start date of the crediting period.

C.8 Permanent changes from MR monitoring plan, applied methodology, or applied standardized baseline

Not applicable.

C.9 Monitoring period number and duration

Total Monitoring Period: 2 Years and 6 months

Date: 01/07/2021 to 31/12/2023 (inclusive of both dates).

C.10 Monitoring Plan

The project activity essentially involves the generation of electricity from wind, the employed WTG only converts wind energy into electrical energy and does not use any other input fuel for electricity generation, thus no special ways and means are required to monitor leakage from the project activity. The recording of the electricity fed to the state utility grid is carried out jointly at the incoming feeder of the state power utility (GETCO).

Data / Parameter	UCR recommended emission factor
Data unit	tCO2 /MWh
Description	As per UCR CoU Standard Aug 2022 (Updated Ver.6), Clause – Emission Factors "The UCR recommends an emission factor of 0.9 tCO2/MWh for the 2013-2020 years as a fairly conservative estimate for Indian projects not previously verified under any GHG program. Emission factors for the post 2020 period are to be selected as the most conservative estimate between the national electricity/power authority published data set and UCR default of 0.9 tCO2/MWh."
Source of data	https://a23e347601d72166dcd6- 16da518ed3035d35cf0439f1cdf449c9.ssl.cf2.rackcdn.com//Documents/ UCRStandardAug2024updatedVer7_020824191534797526.pdf
	https://cea.nic.in/wp- content/uploads/baseline/2024/04/User_GuideVersion_19.0.pdf
Value applied	0.9
Measurement methods and procedures	-
Monitoring frequency	Fixed parameter
Purpose of Data	For the calculation of emission factor of the grid
Additional Comment	The combined margin emission factor as per the CEA database (current version 18, December 2022) results into a higher emission factor. Hence for 2022 vintage UCR default emission factor remains conservative.

Data and Parameters available:

Data and Parameters to be monitored (ex-post monitoring values):

Data / Parameter	EG _{PJ,facility, y}			
Data unit	MWh			
Description	Net electricity supplied to the NEWNE grid facility by the project activity between 01/07/2021 to 31/12/2023.			
Source of data	SLDC Certificate			
Measurement	Data Type: Measured			
procedures (if any):	Monitoring equipment: Energy Meters are used for monitoring Recording Frequency: Continuous monitoring and Monthly recording from Energy Meters, Summarized Annually			
	Archiving Policy: Paper & Electronic Calibration frequency: 5 years (as per CEA provision)			
	The Net electricity generation by the WTG is recorded at the sub-station. At the end of every month, SLDC Certificate is generated based on the total monthly electricity exported to the grid.			
	Meter Calibration Details:			
	Meter No.MakeAccuracyCalibration DateGJ4886BSecure0.208/04/2023			
Measurement Frequency:	Monthly			
Value applied:	11687.709 (Ex-post estimate)			
QA/QC procedures applied:2	Calibration frequency: 5 years (as per CEA provision)			

	Based on the joint meter reading certificates/credit notes, and energy generation report.
	As per Central Electricity Authority (Installation and Operation of Meters) (Amendment) Regulations, 2019, dated 23rd December, 2019.
	<i>Clause 14, point 1, (b)</i> "All Interface Meters shall be tested on-site using accredited test laboratory for routine accuracy testing at least once in five years and recalibrated if required". And
	Point 2, (iii) Energy Accounting and Audit Meters: Energy Accounting and Audit Meters shall be tested at site through accredited test laboratory at least once in five years or whenever the accuracy is suspected or whenever the readings are inconsistent with the readings of other meters, e.g., Check Meters, Standby Meters and defective meters shall be recalibrated, if required: Provided that the testing shall be carried out without removing the Instrument Transformers connection."
Purpose of data:	The Data/Parameter is required to calculate the baseline emission.
Any comment:	Data will be archived electronically for a period of 36 months beyond the end of crediting period.

ANNEXURE I (Emission Reduction Calculation)

2.1 MW wind power project by SVPL													
Month - Wise Energy Delivered to Grid (in MWh)													
Year	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	
2021							579.179	598.531	280.113	185.085	176.978	268.616	
2022	279.623	232.816	330.688	556.043	942.526	672.229	596.366	477.951	334.108	125.327	88.148	207.601	
2023	330.146	193.706	224.57	353.821	716.623	457.19	523.199	928.133	445.28	162.487	151.751	268.875	
Year-Wise Emission reduction calculation for the project activity													
Year	r Total No. of Electricity delivered in MWh				Recommended emission factor tCO2/MWh				Wh	Total CoUs generated			
2021	2088.502				0.9					1879			
2022	4843.426				0.9					4359			
2023	4755.781				0.9					4280			
Total CoUs to be issued for the first monitoring period (Year: 2021-2023)10518.000													